



Programiranje internet aplikacija

Elektrotehnički fakultet, Univerzitet u Beogradu

2025/2026


Uvod

- Deo MEAN steka – *open-source* JavaScript softverski stek

- M – MongoDB
- E – Express
- A – Angular
- N – Node.js



MEAN stack





Node.js

- JavaScript ili TypeScript izvorni kod
 - TypeScript izvorni kod se prevodi u JavaScript kod
 - Asinhroni *event-driven JavaScript enviroment* za izvršavanje na serverskoj strani
 - Jedan proces koji omogućava asinhronone neblokirajuće pozive ka API-jima, čime se omogućava velika konkurentnost bez eksplicitnog *thread management-a*
 - npm *package installer*
- 
- 



Express

- *Backend framework* za posredovanje između Node.js i baze podataka
 - REST API
 - CRUD operacije (create, read, update, delete)
- 
- 

Instalacija, kreiranje i pokretanje aplikacije

- Node.js (22.21.0)
 - <https://nodejs.org/dist/v22.21.0/>


- npm init
 - za entry point staviti dist/server.js

```
npm install typescript --save-dev
npm install @types/node --save-dev
npm install express
npm install @types/express --save-dev
npm install cors
npm install @types/cors --save-dev
npm install mongoose
npm install mongodb
```

```
npx tsc --init --outDir dist
```

} package.json

} tsconfig.json





U package.json izmeniti još i:

```
"scripts": {  
  "test": "echo \"Error: no test specified\" && exit 1"  
},
```

sa:

```
"scripts": {  
  "start": "npm run serve",  
  "serve": "node dist/server.js",  
  "build": "tsc"  
},
```



Struktura projekta i početni kod

> node_modules

✓ src

TS server.ts

{ } package-lock.json

{ } package.json

TS tsconfig.json

```
import express from 'express'
```

```
const app = express()
```

```
app.get('/', (req,res)=> {res.send("Hello world!")})
```

```
app.listen(4000, ()=>console.log('Express running on port 4000'))
```

- app.get – get zahtev
- req – request, res – response
- app.listen – osluškivanje na portu



Pokretanje projekta

- Komanda tsc
 - Kompajlira sve iz src
 - dist folder


```
✓ dist
  JS server.js
  > node_modules
✓ src
  TS server.ts
  {} package-lock.json
  {} package.json
  TS tsconfig.json
```

- Pokretanje – npm run serve

```
● >> npm run serve

> backend@1.0.0 serve
> node dist/server.js

Express server running on port 4000
```



Kontroleri

```
// controllers/user.controller.ts
import express from 'express'
// import modela itd

export class UserController {
  login = (req: express.Request, res: express.Response) => {
    // npr.
    let username = req.body.username;
    let password = req.body.password;
    let result = . . .;

    // . . .
    res.json(result);
  }

  register = (req: express.Request, res: express.Response) => {
    . . .
  }
}
```

Rutiranje

```
// routers/user.router.ts
import express from 'express'
import { UserController } from '../controllers/user.controller';

const userRouter = express.Router();

userRouter.route('/login').post(
  (req, res) => new UserController().login(req, res)
)

export default userRouter;
```



Rutiranje – korišćenje u server.ts

```
const router = express.Router();  
router.use('/users', userRouter)
```

```
// const app = express();  
app.use('/', router);
```



CORS

```
// server.ts
import cors from 'cors' // za cross-origin

// const app = express();
app.use(cors())
app.use(express.json()) // označavamo da podatke šaljemo u JSON formatu
```



HVALA NA PAŽNJI!

